EASY PLUG

PSI Energy™

ใหม่
รองรับอุปกรณ์กันไฟย้อน



คุณสมบัติ

- กำลังไฟสูงสุด 400W
- ป้องกันฝุ่นละออง มาตรฐาน IP50
- ควรติดตั้งไว้ในที่ร่ม
- รองรับอุปกรณ์กันไฟย้อน(CT)
- รองรับแผงโซลาร์เซลล์สูงสุด 450W
- รองรับการใช้งาน Application ผ่านอุปกรณ์เสริม

ใช้ง่าย 3 ขั้นตอน

วางแผง — ต่อสาย — ใช้งาน

TECHNICAL SPECIFICATION

MODEL	EP4
Input	
Max.Input Voltage	50V DC
Range of Peak Power Mppt Voltage	32-49V DC
Range of Input Operating Voltage	22-49 DC
Start-up Voltage	25V DC
Max. continuoue Input Current	13.5A DC
Max. Input Short Circuit Current	15A DC
Output	
Max. Continuous Output Power	395W
Max Continuous Output Current	1.8A AC *
Norminal Output Voltage	190 ~ 240V AC
Norminal Output Frequancy	50Hz
Peak Conversation Effciency	92%
Output Power Factor(adjustable)	>0.97 default
Mechanial Data	
Ambient temperature range	-40~+65°C
Enclosure rating	IP50
Dimensions W x H x D (mm)	207 x 175 x 45 MM
Weight(Kg)	1.56Kg
Effciency	
CEC peak effciency	92%
CEC weighted effciency	91%
Nominal MPPT effciency	99.50%

PSI Official
@PSI1247
PSI
psiofficial
1247 Customer service